






Elastic arm thickness 0.96  
 \*Elastic arm width 0.25+0.1/-0  
 Section Y1-Y1



Scale 1:2

Change record				
Aera	Mark	Change Content Description	Date	Changer/Approve
N/A	N/A	First release	2020-12-07	

Unmarked Dimension Tolerance Table					
>	≤	Plastic	Metal	Diecast	Rubber
0	3	±0.05	±0.05	±0.10	±0.10
3	6	±0.07	±0.05	±0.10	±0.10
6	30	±0.10	±0.10	±0.15	±0.15
30	120	±0.15	±0.15	±0.25	±0.25
120	~	±0.20	±0.20	±0.30	±0.3%
Unmarked Angel Tolerance ±0.5°					



- Four corners are higher than the TP surface 0.12mm;
- The left and right sides are higher than the TP surface 0.5mm;
- The head is higher than the TP surface 0.9mm;
- The bottom is higher than the TP surface 0.3mm;
- Sumprint effect needs to be confirmed with ID.

- Note:
- Material: TPU
  - After each hole position mold is matched, it should be centered as far as possible relative to the hole of the whole machine, and the hole should not be blocked;
  - Dimensions without tolerances are controlled in accordance with the tolerances without tolerance table, marked with \* as key dimensions;
  - Sharp edges, oil stains and deformation are not allowed on the surface of the product;
  - Defects such as sharp edges, oil stains, gaps and deformations are not allowed in the opening;
  - The shape and size of the protective shell ensure that the function is qualified and the whole machine assembly is qualified;
  - The appearance effect meets the requirements of ID CWF documents;
  - The quality of raw materials meets the requirements of RoHS and Reach agreement;
  - Z1-Z4 tolerance range +0~+0.2mm.

<b>oppo</b>		TPU Protect Holder-IND		SU-AA035-PROTECT-HOLDER-TPU_IND			
		Design	2020/12/07	Material		Scale	Version
Check					1:1	1	V1
Standard					Unit	Weight(g)	
Approve			Page	1	mm		