



Change record				
Aera	Mark	Change Content Description	Date	Changer/Approve
N/A	N/A	First release	2020-12-07	

Unmarked Dimension Tolerance Table				
>	≤	Plastic	Metal	Diecut Rubber
0	3	±0.05	±0.05	±0.10
3	6	±0.07	±0.05	±0.10
6	30	±0.10	±0.10	±0.15
30	120	±0.15	±0.15	±0.25
120	~	±0.20	±0.20	±0.30
Unmarked Angel Tolerance ±0.5°				

Elastic arm thickness *0.84±0.10

**Elastic arm width 0.25+0.1/-0

Section Y1-Y1



1. Four corners are higher than the TP surface 0.12mm;
2. The left and right sides are higher than the TP surface 0.5mm;
3. The head is higher than the TP surface 0.9mm;
4. The bottom is higher than the TP surface 0.3mm;
5. Smprint effect needs to be confirmed with ID.

Note:

- 1.Material: TPU
- 2.After each hole position mold is matched, it should be centered as far as possible relative to the hole of the whole machine, and the hole should not be blocked;
- 3.Dimensions without tolerances are controlled in accordance with the tolerances without tolerance table, marked with * as key dimensions;
- 4.Sharp edges, oil stains and deformation are not allowed on the surface of the product;
- 5.Defects such as sharp edges, oil stains, gaps and deformations are not allowed in the opening;
- 6.The shape and size of the protective shell ensure that the function is qualified and the whole machine assembly is qualified;
- 7.The appearance effect meets the requirements of ID CMF documents;
- 8.The quality of raw materials meets the requirements of RoHs and Reach agreement;
- 9.Z1-Z4 tolerance range +0~+0.2mm.

oppo			TPU Protect Holder			SJ-AA035-PROTECT-HOLDER-TPU		
Desi gn		2020/12/07	Material			Scale	Version	Version
Check						1 : 1	1	V1
Standard						Unit	Weight(g)	
Approve			Page		1	mm		